



DRIVE X4

EXTREME PRESSURE AUTOMOTIVE GEAR OIL

PRODUCT DESCRIPTION:

DRIVE X4 is a high-quality gear and transmission lubricant crafted from solvent-refined mineral base oils and specially selected sulfur and phosphorus additives. With excellent shear stability, it provides outstanding gear protection and ensures reliable performance across diverse temperature conditions.

APPLICATION:

DRIVE X4 is recommended for automotive transmission and gear where API GL-4 performance is required. It's also suitable for other automotive type equipment, operated under high speed, low torque and low-speed/high torque conditions.

FEATURES & BENEFITS:

- Excellent lubrication without channeling at low-temperatures.
- Superior protection against rusting, pitting and corrosion.
- Suitable for heavy duty service in truck and bus gears operating at high temperatures.
- Provides good protection against wear.
- Formulated for automotive high speed gears.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	90	140	80W-90	85W-90	80W-140	85W-140	75W-90
API	GL-4	GL-4	GL-4	GL-4	GL-4	GL-4	GL-4
MIL	MIL-L-2105B	MIL-L-2105B	MIL-L-2105B	MIL-L-2105B	MIL-L-2105B	MIL-L-2105B	MIL-L-2105B

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	DRIVE X4						
			90	140	80W-90	85W-90	80W-140	85W-140	75W-90
KV@ 104°F /40°C	D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR	TBR
KV@212°F /100°C	D7042	cSt	17.5	28.3	15.6	17.5	28.5	28.2	14.4
Viscosity Index (min)	D2270	-	95	95	140	140	140	140	140
Density@15°C	D4052	g/cm³	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	200	200	200	200	200	200	200
Pour Point (max)	D97	°C	-9	-9	-27	-15	-27	-12	-42
Brookfield Viscosity	D2983	cp	-	-	<150,000 (-26C)	<150,000 (-12C)	<150,000 (-12C)	<150,000 (-26C)	<150,000 (-40C)

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com

