Automactic Transmission Fluids



Technical Data Sheet

GLIDE TRONIC 9 SPEED AUTOMATIC TRANSMISSION FLUID

PRODUCT DESCRIPTION:

GLIDE Tronic is a high-performance Automatic Transmission Fluid (ATF) engineered with advanced synthetic base oils and premium performance additives. Designed as a service fill fluid, it is specifically formulated for the latest generation of fuelefficient 9-speed automatic transmissions, ensuring smooth operation and enhanced reliability.

APPLICATION:

GLIDE Tronic is recommended for the latest generation of Mercedez-Benz 9-speed automatic transmissions (9G-tronic).

FEATURES & BENEFITS

- · High thermal and oxidative stability.
- · Improved lubricating
- · Outstanding shear stabity
- maximum reduction of fuel consumption, which reduces emission
- · Superior overall performance

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

MB 236.17

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	GLIDE TRONIC
KV@ 104°F /40°C	D7042	cSt	TBR
KV @ 212°F /100°C	D7042	cSt	4.2
Viscosity Index	D2270	-	140
Density@15°C	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-42

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact, Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com

