



## GLIDE UTTO 20W-40 MINERAL

### PRODUCT DESCRIPTION:

GLIDE UTTO is a premium multi-functional oil especially formulated for use in agricultural equipment, engines, transmissions, and differentials with wet brake system and integrated hydraulic system. The carefully chosen base oils and additive system forms a thermal and oxidation stable oil film thus keeps the engine, gear box, differential, and hydraulic system clean and in good condition.

### APPLICATION:

GLIDE UTTO oil is suitable for agricultural machinery in the areas of gearbox, engine, hydraulic systems and immersion brakes for heavy-duty tractors.

### FEATURES & BENEFITS:

- Guarantees easy gear changing
- High pressure-absorption capability
- Stable to oxidation
- High resistance to aging
- Universal application
- Rationalizes storage
- High wear resistance
- Good cold-start behavior

### PERFORMANCE LEVELS: Meets and Exceeds:

- Guarantees easy gear changing
- High pressure-absorption capability
- Stable to oxidation
- High resistance to aging
- Universal application
- Rationalizes storage
- High wear resistance
- Good cold-start behavior

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	GLIDE UTTO
Grade			20W-40
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	120
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	14.9
Viscosity Index	D-2270	-	128
SP. Gravity @15°C/ 60°F	D-4052	g/cm <sup>3</sup>	0.890
Flash Point (min)	D-92	°C	236
Pour Point (max)	D-97	°C	-24

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website phoenixlubricants.com