



WHEELER 2T 2 STROKE ENGINE OIL

PRODUCT DESCRIPTION:

WHEELER 2T is a high-performance lubricant designed for two-stroke engines, including motorcycles, scooters, and mopeds. Its formulation is fully compatible with lead-free fuels, combining highly refined base stocks with the latest additive technology for optimal performance. Specially crafted for both oil-injected and premixed gasoline/oil lubricated engines, WHEELER 2T offers enhanced protection against exhaust emissions and engine carbon deposits, ensuring smoother operation and longer engine life.

APPLICATION:

WHEELER 2T oil is intended for use in two-stroke air cooled engines. Also suitable for motorcycles, scooters, mopeds, snow mobiles, lawn mowers, golf carts, chain saws and other two-stroke powered applications where API TC lubricants are recommended. Product is to be used as per OEM recommended fuel/oil mix ratio. If the specific ratio is not provided, the general recommendation is to use 50:1 fuel/oil mix.

FEATURES & BENEFITS:

- Provides piston scuffing protection and reduces smoke
- Thermal and oxidation stability
- Specially formulated to avoid spark plug fouling
- Perfectly adapted to unleaded fuel
- Protection against pre-ignition problems

PERFORMANCE LEVEL: Meets or Exceeds:

- API TC
- JASO FD
- ISO EGD

TYPICAL PROPERTIES:

| PARAMETERS | TEST METHOD | UNIT | WHEELER 2T |
|------------------------------------|-------------|-------------------|------------|
| Kinematic Viscosity @ 104°F /40°C | ASTM D7042 | cSt | TBR |
| Kinematic Viscosity @ 212°F /100°C | ASTM D7042 | cSt | 9 |
| Viscosity Index | ASTM D2270 | - | 120 |
| Density@15°C/ 60°F | ASTM D4052 | g/cm ³ | TBR |
| Flash Point (min) | ASTM D92 | °C | 220 |
| Pour Point (max) | ASTM D97 | °C | -24 |
| Color | Visual | - | Blue |

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com