WHEELER 4T PLUS SAE 40 SYNTHETIC

PRODUCT DESCRIPTION:

Wheeler 4T Plus SAE 40 is mineral based engine oil recommended for 4T engine motorcycle. Wheeler 4T optimizes engines performance, fuel economy and engine cleaning requirements. It's also offers excellent engine protection and superior clutch operation for daily use.

APPLICATION:

Wheeler 4T is recommended for all 4T engine motorcycles. It is made by blending selected mineral base oil and optimized additives. It has good oxidation stability under high temperature.

FEATURES & BENEFITS:

- · High thermal and oxidative stability.
- Provides good friction on clutch disc, preventing slippage and premature wear in joint engine and transmission (wet clutch) lubrication system
- Environment friendly.
- · Exhibits easier cold weather starting.
- · Good compatibility with rubber to Protect rubber seals.

PERFORMANCE LEVELS: Meets or Exceeds:

API CD

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	WHEELER 2T
SAE Grade			40
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	132.6
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	14.0
Viscosity Index	D-2270	-	103
SP. Gravity @15°C/60°F	D-4052	g/cm³	0.890
Flash Point (min)	D-92	°C	240
Pour Point (max)	D-97	°C	-12
TBN	D-2896	Mg KOH/g	7

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com



