



## DEOTEC X-MAX SEMI SYNTHETIC

### PRODUCT DESCRIPTION:

DEOTEC X-MAX is a high performance, diesel engine oil specifically formulated to address the needs of high power engines. Featuring an active-detergent system to keep pistons and other engine parts clean thus it provides protection against wear for long engine life and protection against deposits for efficient engine performance. These are diesel engine oils specially designed to meet the requirements of engines produced by all manufactures in US, Europe and Japan.

### APPLICATION:

Recommended for wide range of turbo-charged or naturally aspirated diesel engines, generators, trucks, construction cars, passenger cars or mixed car group comprising diesel and gasoline cars. It is also recommended for automotive diesel engine of passenger cars and light commercial vehicles where the OEM recommends API CF-4 or earlier specification.

### FEATURES & BENEFITS:

- Fuel saving and reduces maintenance expenses for machines and engines.
- Very long oil changing period.
- Resists oil thickening and the formation of carbon, varnish and sludge deposits.
- Good viscosity control.
- Prolonged engine life.
- Safeguards the moving parts.
- Keeps engine Clean.

### PERFORMANCE LEVELS: Meets and Exceeds

- API CF-4/SJ
- MB 228.2
- ACEA E2-96, A3/B3
- MTU Type-2
- MAN 3275-1
- VOLVO VDS
- MACK EO/K2
- CES 20075/74/73

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	DEOTEC X-MAX	
			10W-30	10W-40
Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	11.7	15.6
Viscosity Index (min)	D2270	-	145	145
Density@15°C/ 60°F	D4052	g/cm <sup>3</sup>	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-36	-36

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [Phoenixlubricants.com](http://Phoenixlubricants.com)