



GLIDE Plus II

MINERAL

PRODUCT DESCRIPTION:

GLIDE Plus II is an automatic transmission oil blended with highly refined base stocks and one of the latest additive's technologies. It is used in passenger cars and light commercial vehicles. It helps reduce transmission "chatter" assuring a smooth and quiet operation at all speeds under any working condition. Drive II provides optimal oxidation and thermal stability, friction control, cleanliness, load carrying ability, wear and corrosion protection to ensure the longest life of your transmission.

APPLICATION:

Suitable for automatic gearboxes of passenger cars, vans, truck and buses where the manufacturer recommends an ATF GM Dexron II D.

FEATURES & BENEFITS:

- Very high viscosity index linked with an excellent viscosity stability in operation
- Very low pour point
- Very good thermal stability
- Excellent resistance to oxidation
- Friction properties specific to the requirements of GENERAL MOTORS Hydramatic

PERFORMANCE LEVELS: Meets or Exceeds:

- GM DEXRON IID/IIIE • ALLISON TES 389, ALLISON TES 228(C4)
- FORD ESP-M2C138-CJ / ESP-M2C166-H • MAN 339 TYPE L1/L2/Z1/V1 • CHRYSLER +3
- TASA • VOITH H55.6335 • VOLVO CE 97340/41 • MB 236.1/236.5/236.7236.8
- ZF TE-ML-03D / 05 / 21L / 09 / 11A / 11B / 14A / 17C • TOYOTA TII/2
- BMW 81 22 9 400 272/81 22 9 400 275/81 22 9 407 738 • CAT TO-2
- OPEL 19 40 700 / 19 40 707 • MITSUBISHI SP / SP2/ BTR

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	GLIDE Plus II
Grade			
Kinematic Viscosity @ 104° F / 40° C	ASTM D-7042	cSt	34
Kinematic Viscosity @ 212° F / 100° C	ASTM D-7042	cSt	7.0
Viscosity Index (min)	ASTM D-2270	-	170
SP. Gravity @15° C/ 60° F	ASTM D-4052	g/cm ³	0.868
Flash Point (min)	ASTM D-92	°C	200
Pour Point (max)	ASTM D-97	°C	-42

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com