



## WHEELER 4T XP

SYNTHETIC / SEMI SYNTHETIC

### PRODUCT DESCRIPTION:

WHEELER 4T XP is a high-performance engine oil designed specifically to meet the demanding requirements of motorcycle engines. While primarily intended for on-road, high-performance 4-cycle sport bikes, it is also suitable for various on and off-road 4-cycle motorcycles. This oil is specially formulated to provide exceptional protection for 4-cycle, V-Twin engines, especially those that are air-cooled and operate at higher temperatures. WHEELER 4T XP offers excellent performance in engines with combined engine/transmission lubrication systems or separate engine and transmission lubrication systems.

### APPLICATION:

Recommended for all 4-Stroke motorcycles including cruisers and off-road motorcycles.

### FEATURES & BENEFITS:

- Excellent shear stability
- Provides high temperature protection
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Excellent wear and corrosion protection
- Maximizes power and acceleration
- Added protection against harmful deposits

### PERFORMANCE LEVELS: Meets or Exceeds:

- API SN
- JASO MA2

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	WHEELER 4T XP				
Grade			5W-40	10W-30	10W-40	10W-50	10W-60
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	14.5	12	14.1	19.2	25.6
Viscosity Index (min)	D2270	-	160	140	145	155	165
Density@15°C/ 60°F	D4052	g/cm <sup>3</sup>	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220	220	220
Pour Point (max)	D97	°C	-39	-36	-36	-36	-36
TBN	D2896	mg KOH/g	7	7	7	7	7
CCS	D5293	m.Pa.S	<6600 (-30°C)	<7000 (-25°C)	<7000 (-25°C)	<7000 (-25°C)	<7000 (-25°C)

**DISCLAIMER:** The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [Phoenixlubricants.com](http://Phoenixlubricants.com)

