



IGNITE EXTRA MINERAL

PRODUCT DESCRIPTION:

IGNITE EXTRA mineral oils are crafted from high-quality base stocks and advanced performance additives to deliver reliable engine protection and performance across diverse operating conditions. These oils are recommended for high-performance gasoline engine vehicles, including those equipped with direct injection, multi-valve systems, and turbocharger technologies.

APPLICATION:

Recommended for gasoline fueled automobiles and light duty trucks requiring an API SN.

FEATURES & BENEFITS:

- Excellent engine cleanliness
- Engine protection under a wide variety of operating conditions
- Optimum power & performance under most severe driving conditions
- Fully compatible with all emission control devices and all gasoline grades
- Helps reduce engine wear and corrosion

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API SN/CF
- ACEA A3/B3/B4
- MB 229.1
- VW 505 00

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	IGNITE EXTRA	
Grade			15W-40	20W-50
Kinematic Viscosity @ 104°F /40°C	D445	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D445	cSt	15.1	19.9
Viscosity Index (min)	D2270	-	140	130
Density@15°C/ 60°F	D4052	g/cm ³	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-33	-24

DISCLAIMER: The test data provided above is for reference purposes and is not a strict specification, as variations within acceptable production tolerances may occur. Phoenix reserves the right to update or revise this test data. For the most accurate and up-to-date information, please consult the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Phoenixlubricants.com

